

# FAST Push-pad

## Technical features

- Painted aluminium alloy cover.
- Deadlocking chrome-plated aluminium alloy latchbolt.

## Standard configuration operation

- From the inside: by pushing the pad.
- From the outside: with the key and/or handle\*.

## Hand

0 = non-handed.

## Supplied as standard

- Special strikers.
- Fixing screws.
- Installation and maintenance instructions.
- ICIM and CE certificates of compliance.

## On request:

- Outside access devices.
- Extended bolts.
- Version with hold open device (spec. FG).
- Fire door version with steel latchbolts (spec. FG).



## Certifications and markings

- CE marking in accordance with Construction Products Regulation EU 305/2011, issued by ICIM.
- Voluntary product certification issued by the independent certifying body ICIM according to UNI EN 179.

# FAST Flow

System with no floor striker The door opens freely when the deadbolt is withdrawn, thanks to a special system that keeps the rods inside the door.

## Technical features

- Painted aluminium/aluminium alloy cover.
- Chrome-plated aluminium alloy deadbolts.
- Forward stroke 13.5 mm.
- Deadbolt diameter 15 mm.
- Patented deadbolt locking system.
- Adjustable strikers for overlap height 10 mm - 20 mm (patented system).

## Standard configuration operation

- From the inside: by pushing the bar, the deadbolts withdraw
- From the outside: with the key and/or handle\*.

## Hand

0 = non-handed.

## Supplied as standard

- Deadbolt extension kit
- Special strikers.
- Fixing screws.
- Installation and maintenance instructions.
- ICIM and CE certificates of compliance.



## On request:

- Horizontal bar.
- Outside access devices.

## Certifications and markings

- CE marking in accordance with Construction Products Regulation EU 305/2011, issued by ICIM.
- Voluntary product certification issued by the independent certifying body ICIM according to UNI EN 1125..